



GASOLINE ENGINE



**PEDESTAL MOUNTED
for flexible coupling**



**FLEXIBLE COUPLED
TO ELECTRIC DRIVE**

HORIZONTAL . . . LONG or CLOSE COUPLED FOR:

WATER OR SALT WATER

- **MATERIALS -**
Pump casing made of rugged glass reinforced polyester
Buna-N elastomers and stainless steel fasteners
- **FLOW RATES ELECTRIC MOTOR DRIVEN**
To 380 U.S. GPM or 88 ft. TDH @ 60 Hz
(To 1198 LPM or 18.6m TDH @ 50 Hz)
- **FLOW RATES GASOLINE ENGINE DRIVEN**
To 360 U.S. GPM or 83 ft. TDH
(To 1360 LPM or 25.3m TDH)
- **WILL LIFT 25 ft. (7.6m) VERTICAL***
- **2" or 3" PORTS**
- **CLOSE COUPLED TO GASOLINE ENGINE, LONG COUPLED TO ELECTRIC MOTOR OR PEDESTAL MOUNTED FOR FLEXIBLE COUPLING**
- **BUILT-IN CHECK VALVE**

Series 'T' Self-Priming Centrifugal Pumps are lightweight, chemically resistant pumps for general service on water, salt water and mildly corrosive liquids containing solids. They will pass a solid 1/3 the diameter of the suction port. 'T' Pumps feature tough non-metallic impeller, steel volute and wearplate with non-metallic coating, 316 stainless steel internal fasteners and 304 stainless steel quick release housing clamp. Housing is rugged glass reinforced polyester. Pressurized oil lubrication system protects hard silicon carbide shaft seal faces. "O"-rings and gasket are Buna-N. Engine driven pumps include spring mounted base rails.

All pumps include a built-in check valve, feature easy servicing and during pumping, a self-cleaning double volute keeps pump free of settled solids.

*Based on water-like liquids at 70°F and at 3450 RPM after initial priming of pump housing.

SERIES 'T' SELF-PRIMING PUMP specifications



GASOLINE ENGINE


PUMP WITH GASOLINE ENGINE DRIVE OR WITH PEDESTAL ONLY

Pump molded of glass reinforced polyester. Molded non-metallic impeller. Volute and wearplate are steel with molded non-metallic, abrasion resistant coating. 304 stainless steel housing clamp, 316 stainless steel internal fasteners, Buna-N "O"-rings and gasket, check valve, oil lubricated single mechanical seal with hard silicon carbide faces. Engine driven pumps include heavy duty engine with dual element air cleaner, threaded pipe fittings, suction strainer, carrying handle and spring mounted base rails.

See Bulletin P-633 for components required for long coupling to electric drive motors.





PEDESTAL MOUNTED



FLEXIBLE COUPLED TO ELECTRIC DRIVE


| FLOW CURVE LETTER | PORT SIZE | MAX. FLOW 3800 RPM | | MAX. TDH 3800 RPM | | SHIP. WT | MODEL NUMBER | PRICE CODE NO. | GASOLINE ENGINE | | PEDESTAL (CAST IRON) | | | |
|----------------------------------|-----------|--------------------|------|-------------------|------|----------|--------------|----------------|-----------------|-------|-----------------------------------|-----|--------|--|
| | | IN. | GPM | LPM | FT. | | | | m | LBS | ADD TO MODEL & PRICE CODE NO. . . | | ADD TO | |
| | | | | | | | | | | | MODEL | PCN | | |
| Q | 2 | 240 | 900 | 83 | 25.3 | 90 | TE2QBB GK | 64-72Q8 GK | -E5AC | - | - | | | |
| T | 3 | 360 | 1360 | 80 | 24.4 | 110 | TE3TBB GK | 64-73T8 GK | -E8AC | - | - | | | |
| HORSEPOWER REQUIRED / RPM | | | | | | | | | | | | | | |
| B | 2 | 120 | 450 | 28 | 8.5 | 65 | TE2BBB | 64-72B8 | .61 / 3450 | -CSS | P | | | |
| D | 3 | 180 | 680 | 23 | 7.0 | 76 | TE3DBB | 64-73D8 | .9 / 3450 | -CTSS | P3 | | | |
| K | 2 | 240 | 900 | 88 | 26.8 | 65 | TE2KBB | 64-72K8 | 4.0 / 3450 | -CSS | P | | | |
| M | 3 | 380 | 1440 | 73 | 22.3 | 76 | TE3MBB | 64-73M8 | 6.0 / 3450 | -CTSS | P3 | | | |

FLOW CURVES



F.O.B. Northbrook Illinois

Specifications subject to change without notice.



SERFILCO, LTD.

2900 MacArthur Blvd. 847-509-2900
 Northbrook, IL 60062-2005 U.S.A. 800-323-5431
 e-mail: sales@serfilco.com FAX: 847-559-1995
 www.serfilco.com